

ED series

Drying ovens with natural convection

Routine drying and sterilization applications up to 300 °C (572 °F) and storage at precisely controlled elevated temperatures are the strengths of ED drying ovens. Because of the natural convection with a high rate of air exchange, thermal processes run with significantly increased efficiency.

**Leistungsmerkmale/Ausstattung:**

- Electronically-controlled APT.line™ preheating chamber technology with natural convection
- Temperature range of 5 °C (9 °F) above ambient temperature up to 300 °C (572 °F)
- DS controller with integrated timer 0 to 99 hours
- Digital temperature setting with an accuracy of one degree
- One ramp function
- Independent adjustable temperature safety device, Class 2 (DIN 12880), with visual temperature alarm
- Adjustable ventilation by means of rear exhaust duct Ø 50 mm (2 inch) with ventilation flap and front ventilation slide
- Optional RS 422 interface for communication software APT-COM™ DataControlSystem
- 2 chrome-plated racks
- Units up to 115 liters (4.1 cu.ft.) are stackable
- BINDER test certificate
- **Only at BINDER: Precision regardless of size – the 20-liter (0.7 cu.ft.) bench-top units.**

	ED 23	ED 53	ED 115	ED 240	ED 400	ED 720
Exterior dimensions						
Width (mm/inch)	433 / 17.1	634 / 25.0	834 / 32.8	1034 / 40.7	1234 / 48.6	1234 / 48.6
Height (inclusive feet/castors) (mm/inch)	492 / 19.4	617 / 24.3	702 / 27.6	822 / 32.4	1022 / 40.2	1528 / 60.2
Depth (mm/inch)	516 / 20.3	575 / 22.6	645 / 25.4	745 / 29.3	765 / 30.1	865 / 34.1
plus door handle, l-panel and exhaust duct (mm/inch)	85 / 3.4	85 / 3.4	85 / 3.4	85 / 3.4	85 / 3.4	85 / 3.4
Wall clearance rear (mm/inch)	100 / 3.9	100 / 3.9	100 / 3.9	100 / 3.9	100 / 3.9	100 / 3.9
Wall clearance side (mm/inch)	100 / 3.9	160 / 6.3	160 / 6.3	160 / 6.3	160 / 6.3	160 / 6.3
Exhaust duct outer-Ø (mm/inch)	52 / 2.1	52 / 2.1	52 / 2.1	52 / 2.1	52 / 2.1	52 / 2.1
Steam space volume (l/cu.ft.)	36 / 1.3	70 / 2.5	142 / 5.0	283 / 10.0	457 / 16.2	808 / 28.6
Number of doors	1	1	1	2	2	2
Interior dimensions						
Width (mm/inch)	222 / 8.7	400 / 15.8	600 / 23.6	800 / 31.5	1000 / 39.4	1000 / 39.4
Height (mm/inch)	330 / 13.0	400 / 15.8	480 / 18.9	600 / 23.6	800 / 31.5	1200 / 47.2
Depth (mm/inch)	277 / 10.9	330 / 13.0	400 / 15.8	500 / 19.7	500 / 19.7	600 / 23.6
Interior volume (l/cu.ft.)	20 / 0.7	53 / 1.9	115 / 4.1	240 / 8.6	400 / 14.3	720 / 25.7
Racks, chrome-plated (number standard/max.)	2/3	2/5	2/6	2/7	2/10	2/16
Load per rack (kg/lbs.)	12 / 26	15 / 33	20 / 44	30 / 66	35 / 77	45 / 99
Permitted total load (kg/lbs.)	25 / 55	40 / 88	50 / 110	70 / 155	90 / 199	120 / 265
Weight of the unit (empty) (kg/lbs.)	22 / 49	42 / 93	57 / 126	86 / 190	125/276	174 / 384
Temperature data						
Temperature range, 5°C (9°F) above ambient up to (°C/°F)	300 / 572	300 / 572	300 / 572	300 / 572	300 / 572	300 / 572
Temperature variation 1)						
at 70 °C (158 °F) (± °C)	1,5	2	1,5	1,5	1,7	1,5
at 150 °C (302 °F) (± °C)	2,5	3,2	2,5	2,5	3	2,8
at 300 °C (572 °F) (± °C)	3,8	4,5	4,5	5,0	5,0	5,0
Temperature fluctuation (± °C) at 70°C	0.3	0,3	0,3	0,3	0,3	0,3
Heating up time 2)						
to 70 °C (158 °F) (Min.)	13	14	15	40	49	56
to 150 °C (302 °F) (Min.)	24	27	29	48	62	69
to 250 °C (482 °F) (Min.)	35	61	66	61	74	80
Recov. time after door was opened for 30 sec. 2)						
at 70 °C (158 °F) (Min.)	2,5	2	2	5	4	4
at 150 °C (302 °F) (Min.)	5	6	9	13	20	14
at 300 °C (572 °F) (Min.)	8	11	14	18	24	18
Air change 3)						
at 150 °C (302 °F) (x/h)	13	19	10	10	10	9
Electrical data						
Housing protection acc. to EN 60529	IP 20	IP 20	IP 20	IP 20	IP 20	IP 20
Nominal voltage (±10 %) 50/60 Hz (V)	230 / 115	230 / 115	230 / 115	230 / 208 (3N)	400 / 208 (3N)	400 / 208 (3N)
Nominal power (W)	800	1200	1600	2700	3400	5000
Energy consumption						
at 70 °C (158 °F) (W)	43	60	90	143	201	220
at 150 °C (302 °F) (W)	148	210	300	447	672	750
at 300 °C (572 °F) (W)	450	600	360	700	1000	1200

1) value without window

2) up to 98 % of the set value

3) The air change depends on the inner chamber- and ambient temperature and is subject to significant individual variance. The indicated air change rate represents average values for standard equipment. Individual measurement of air change rate in acc. to ASTM D 5374 are optionally available.

All technical specification are specified for units with standard equipment at an ambient temperature of 25 °C (77 °F) and a voltage fluctuation of ± 10 %. The temperature data are determined in accordance to factory standard following DIN 12880, part 2 respecting the recommended wall clearances of 10 % of the height, width and depth of the inner chamber. All indications are average values, typical for units produced in series. We reserve the right to alter technical specifications at all times.



Access ports

With silicon plugs for inserting external measuring devices into the chamber. Access ports with 10, 30, 50 mm (0.4, 1.2, 2 inch) diameter.



Door with window and interior lighting

For optimum process control in the interior, available for all equipment sizes.



Lockable door

Prevents unauthorized access and interference with processes in the chamber.



Calibration certificates and validation

BINDER can significantly reduce the time and effort needed for equipment qualification. We draw on unparalleled knowledge of our equipment applications and years of experience in certification.




Transportable precision measuring unit

For temperature, using a PT 100 temperature sensor. Suitable for universal use as an independent monitoring device for temperature chambers.



Reinforced inner chamber

Includes two reinforced racks for heavy loads. (Total load maximum 250 kg / 551 lbs.)



Serial printer

For recording temperature data. Suitable for connection to an RS 232 printer interface. Includes cables for the RS 422 interface and an interface converter.



Increased air change rate

Higher capacity air turbine (+ approx. 280 %)

	ED 23	ED 53	ED 115	ED 240	ED 400	ED 720
Access port with silicone plug	O	O	O	O	O	O
Rack, chrome-plated or stainless steel	O	O	O	O	O	O
Shelf, perforated, stainless steel	O	O	O	O	O	O
Indep. adj. temp. safety device, Class 3.1 (DIN 12880) 230/400 V only	O	O	O	O	O	O
Door with window and interior lighting	O	O	O	O	O	O
Lockable door	O	O	O	O	O	O
Door gasket, viton (temperature-resistant up to 200 °C / 392 °F)	O	O	O	O	O	O
Over-temperature alarm, acoustic, can be switched off	O	O	O	O	O	O
Analogue temperature output, 4–20 mA, with 6-pin DIN socket	O	O	O	O	O	O
RS 422 interface	O	O	O	O	O	O
Calibration certificate	O	O	O	O	O	O
Extension for calibration certificate (additional values)	O	O	O	O	O	O
Stable table on castors with locking brakes	-	O	O	O	O	-
Evaporating dish with rim	O	O	O	O	O	O
Rubber pads for safe stacking	O	O	O	O	-	-

O Option - not available

Technical specifications subject to change

BINDER GmbH Postfach 102 D-78502 Tuttlingen **Direction:** Im Mittleren Ösch 5 D-78532 Tuttlingen
Contact: Phone: +49 (0) 74 62/2005-0 | Fax: +49 (0) 74 62/2005-100 | info@binder-world.com | www.binder-world.com